

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курган (3522)50-90-47
Курск (4712)77-13-04
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Ноябрьск (3496)41-32-12
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саранск (8342)22-96-24
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47

syn@nt-rt.ru || <https://sonymed.nt-rt.ru>

MW E-15NMW

Medical

To uchScreen



Model	MWE-15NMW
Display	15.0" diagonal
Aspect Ratio	4:3
Useful Screen Area	Horizontal: 12.0" (304 mm) Vertical: 9.0" (228 mm)
Native (Optimal) Resolution	1024 x 768 at 60 Hz
Other Supported Resolutions	1024 x 768 at 60, 65, 70 or 75 Hz 832 x 624 at 75 Hz 800 x 600 at 56, 60, 72 or 75 Hz 720 x 400 at 70 Hz 720 x 350 at 70 Hz 640 x 480 at 60, 66 (Mac), 72 or 75 Hz
Colors	16.2 million
Brightness (Typical)	LCD panel: 350 nits AccuTouch: 287 nits IntelliTouch: 322 nits
Response Time - Total (Typical)	8 msec
Viewing Angle (Typical)	Horizontal: ±75° or 150° total Vertical: 75°/50° or 125° total
Contrast Ratio (Typical)	400:1
Speakers	Two watt/channel speakers located in display head
On-Screen Display (OSD)	Controls (side): menu, up, down, select, power Settings: contrast , brightness, V-position, H-position, RGB, volume, sharpness, phase, clock, OSD H-position, OSD V-position, OSD time, auto adjust, input select Languages: English, French, German, Spanish, Japanese Lockouts: power, user controls
Input Video Format	Analog VGA, DVI-D
Input Video Signal Connector	Mini D-Sub 15-Pin VGA type, DVI-D connector
Input Frequency	Horizontal: 31–60 kHz Vertical: 56–75 Hz
Power Supply	External DC (power brick)
Input Voltage	AC: 100–240 VAC, 50/60 Hz DC: 12.0 V±0.75 V
Input Connector	AC: IEC 60320 C6 DC: Coaxial power jack (2.5 mm pin diameter, 6.3 mm barrel diameter, 9.5 mm barrel length)
Power Consumption (typical)	48W

Weight	With power adapter: 16.1 lb (8.3 kg) Without power adapter: 15.3 lb (6.9 kg) Actual without stand: 10.8 lb (4.8 kg) Shipping: 22.2 lb (10.1 kg)
Temperature	Operating: 0°C to 40°C (32°F to 104°F) Storage: -20°C to 60°C (-4°F to 140°F)
Humidity (noncondensing)	Operating: 20%-80% Storage: 5%-95%
Form Factor	Desktop
Enclosure Color	Dark gray, beige
MTBF	50,000 hours demonstrated
Stand Options	Tilt, remove
Mounting Options	75 mm VESA mount
Sealing	Touchscreen sealed to bezel Touchscreen sealed to LCD
Other Features	Energy save mode (less than 6 watts) 2 stage DPMS VESA DDC, Plug & Play Security lock receptacle